




Features

- ◇ For surface mounted application
- ◇ Glass passivated junction chip.
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easy pick and place
- ◇ High surge current capability
- ◇ Plastic material used carries Underwriters Laboratory Classification 94V-0
- ◇ High temperature soldering: 260°C / 10 seconds at terminals
- ◇ High reliability grade (AEC Q101 qualified)

Mechanical Data

- ◇ Case: Molded plastic
- ◇ Terminals: Pure tin plated, lead free solderable per J-STD-002B and JESD22-B102D.
- ◇ Polarity: Indicated by cathode band
- ◇ Packaging: 12mm tape per EIA STD RS-481
- ◇ Weight: 0.064 gram

SMA/DO-214AC



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.
 Single phase, half wave, 60 Hz, resistive or inductive load.
 For capacitive load, derate current by 20%

Type Number	Symbol	M1X	M2X	M3X	M4X	M5X	M6X	M7X	Units	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V	
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V	
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V	
Maximum Average Forward Rectified Current @ $T_L = 110^\circ C$	$I_{(AV)}$	1.0							A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	40							30	A
Maximum Instantaneous Forward Voltage @ 1.0A	V_F	1.1							V	
Maximum DC Reverse Current @ $T_A = 25^\circ C$ at Rated DC Blocking Voltage @ $T_A = 125^\circ C$	I_R	5.0 50							μA μA	
Typical Reverse Recovery Time (Note 1)	T_{rr}	1.5							μS	
Typical Junction Capacitance (Note 2)	C_j	12							pF	
Non-Repetitive Peak Reverse Avalanche Energy at 25°C, $I_{AS}=1A$, $L=10mH$	E_{AS}	5							mJ	
Typical Thermal Resistance (Note 3)	$R_{\theta JL}$ $R_{\theta JA}$	27 75					30 85		$^\circ C/W$	
Operating Temperature Range	T_J	-55 to +150							$^\circ C$	
Storage Temperature Range	T_{STG}	-55 to +150							$^\circ C$	

- Notes:
1. Reverse Recovery Test Conditions: $I_F=0.5A$, $I_R=1.0A$, $I_{RR}=0.25A$
 2. Measured at 1 MHz and Applied $V_r=4.0$ Volts
 3. Measured on P.C. Board with 0.2" x 0.2" (5.0mm x 5.0mm) Copper Pad Areas.



RATINGS AND CHARACTERISTIC CURVES (M1 THRU M7X)

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- TYPICAL REVERSE CHARACTERISTICS




FIG.3- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.5- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE






FIG.6- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



NOTES: 1. Rise Time=7ns max. Input Impedance= 1 megohm 22pf
 2. Rise Time=10ns max. Source Impedance= 50 ohms