

Features

- The plastic package carries UL Flammability Classification 94V-0
- For surface mounted applications
- Low reverse leakage
- Built-in strain relief, ideal for automated placement
- High forward surge current capability
- High temperature soldering guaranteed: 260°C/10 seconds at terminals

Mechanical Characteristics

- Case: SMB (DO-214AA) package molded plastic body over passivated chip
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any

Electrical Parameters


PARAMETER		SYMBOL	MURS460	UNIT
Maximum repetitive peak reverse voltage		V_{RRM}	600	V
Maximum RMS voltage		V_{RMS}	420	V
Maximum DC blocking voltage		V_{DC}	600	V
Maximum average forward rectified current		I_{AV}	4	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load		I_{FSM}	100	A
Maximum instantaneous forward voltage at 4A		V_F	1.28	V
Maximum DC reverse current at rated DC blocking voltage	$T_A=25\text{ }^{\circ}\text{C}$	I_R	5	uA
	$T_A=100\text{ }^{\circ}\text{C}$	I_{RT}	50	uA
Maximum reverse recovery time (NOTE 1)		t_{rr}	48	ns
Typical junction capacitance (NOTE 2)		C_J	75	pF
Typical Thermal Resistance Junction to Ambient (NOTE3)		$R_{\theta JA}$	65	$^{\circ}\text{C/W}$
Typical Thermal Resistance Junction to Lead (NOTE3)		$R_{\theta JL}$	20	$^{\circ}\text{C/W}$
Operating Temperature Range		T_J	-55 to 150	$^{\circ}\text{C}$
Storage Temperature Range		T_{STG}	-55 to 150	$^{\circ}\text{C}$

Note1: Reverse recovery condition $I_F=0.5A, I_R=1.0A, I_{rr}=0.25A$

Note2: Measured at 1MHz and applied reverse voltage of 4.0V DC.

Note3: PCB. mounted with 7x7mm copper pad areas

Package Outline Dimensions in inches (millimeters)



Part Marking System



Cathode Band
(for uni-directional products only)

PDW:Company Logo
XX:Marking Code

Summary of Packing Options

Package	Packing Description	Packing Quantity
SMB	Tape/Reel,13" reel	3000