


Working Voltage: 8.5 V
SMA/ DO-214AC
Peak Pulse Power: 400 W

Features

- Glass passivated chip
- 400 W peak pulse power capability with a 10/1000 μ s waveform, repetitive rate (duty cycle):0.01 %
- Low leakage
- Uni and Bidirectional unit
- Excellent clamping capability
- Very fast response time
- RoHS compliant

Mechanical Data

- Case: Molded plastic
- Epoxy: UL 94V-0 rate flame retardant
- Lead: Solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end except Bipolar
- Mounting position: Any



Maximum Ratings($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak power dissipation with a 10/1000 μ s waveform ⁽¹⁾	P_{PP}	400	W
Peak pulse current with a 10/1000 μ s waveform ⁽¹⁾	I_{PP}	See Next Table	A
Power dissipation on infinite heatsink at $T_L = 75^{\circ}\text{C}$	P_D	1.0	W
Peak forward surge current, 8.3 ms single half sine-wave unidirectional only ⁽²⁾	I_{FSM}	40	A
Maximum instantaneous forward voltage at 25 A for unidirectional only ⁽³⁾	V_F	3.5/5.0	V
Operating junction and storage temperature range	T_J, T_{STG}	- 55 to +150	$^{\circ}\text{C}$

Note:

(1)Non-repetitive current pulse per Fig.5 and derated above $T_A=25^{\circ}\text{C}$ per Fig.1

(2)Measured on 8.3 ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum

(3) $V_F<3.5\text{V}$ for devices of $V_{BR}<200\text{V}$ and $V_F<5.0\text{V}$ for devices of $V_{BR}>201\text{V}$

Ratings and Characteristics Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)




Fig. 1 - Pulse Derating Curve




Fig. 2 - Maximum Non-Repetitive Surge Current




Fig. 3 - Steady State Power Derating Curve




Fig. 4 - Peak Pulse Power Rating Curve




Fig. 5 - Pulse Waveform




Fig. 6 - Typical Junction Capacitance

Electrical Characteristics($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Part Number (Bi)	Device Marking Code	Breakdown Voltage V_{BR} @ I_T			Maximum Reverse Leakage I_R @ V_{RWM} (μA)	Working Peak Reverse Voltage V_{RWM} (V)	Maximum Reverse Surge Current I_{PP} (A)	Maximum Clamping Voltage V_C @ I_{PP} (V)
	Bi	Min (V)	Max (V)	I_T (mA)				
SMAJ5.0CA	WE	6.40	7.00	10	800	5.0	43.48	9.2
SMAJ6.0CA	WG	6.67	7.37	10	800	6.0	38.83	10.3
SMAJ6.5CA	WK	7.22	7.98	10	500	6.5	35.71	11.2
SMAJ7.0CA	WM	7.78	8.60	10	200	7.0	33.33	12.0
SMAJ7.5CA	WP	8.33	9.21	1	100	7.5	31.01	12.9
SMAJ8.0CA	WR	8.89	9.83	1	50	8.0	29.41	13.6
SMAJ8.5CA	WT	9.44	10.40	1	10	8.5	27.78	14.4
SMAJ9.0CA	WV	10.00	11.10	1	5	9.0	25.97	15.4
SMAJ10CA	WX	11.10	12.30	1	5	10.0	23.53	17.0
SMAJ11CA	WZ	12.20	13.50	1	1	11.0	21.98	18.2
SMAJ12CA	XE	13.30	14.70	1	1	12.0	20.10	19.9
SMAJ13CA	XG	14.40	15.90	1	1	13.0	18.60	21.5
SMAJ14CA	XK	15.60	17.20	1	1	14.0	17.24	23.2
SMAJ15CA	XM	16.70	18.50	1	1	15.0	16.39	24.4
SMAJ16CA	XP	17.80	19.70	1	1	16.0	15.38	26.0
SMAJ17CA	XR	18.90	20.90	1	1	17.0	14.49	27.6
SMAJ18CA	XT	20.00	22.10	1	1	18.0	13.70	29.2
SMAJ19CA	XB	21.10	23.30	1	1	19.0	13.00	30.8
SMAJ20CA	XV	22.20	24.50	1	1	20.0	12.35	32.4
SMAJ22CA	XX	24.40	26.90	1	1	22.0	11.27	35.5
SMAJ24CA	XZ	26.70	29.50	1	1	24.0	10.28	38.9
SMAJ26CA	YE	28.90	31.90	1	1	26.0	9.50	42.1
SMAJ28CA	YG	31.10	34.40	1	1	28.0	8.81	45.4
SMAJ30CA	YK	33.30	36.80	1	1	30.0	8.26	48.4
SMAJ33CA	YM	36.70	40.60	1	1	33.0	7.50	53.3
SMAJ36CA	YP	40.00	44.20	1	1	36.0	6.88	58.1

Note:

1. Suffix 'A' denotes 5% tolerance device. Without 'A' denotes 10% tolerance device
2. Add suffix 'CA' after part number to specify Bi-directional devices
3. For Bi-Directional devices having V_R of 10 volts and under, the I_R limit is double

Electrical Characteristics($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Part Number (Bi)	Device Marking Code	Breakdown Voltage V_{BR} @ I_T			Maximum Reverse Leakage I_R @ V_{RWM} (μA)	Working Peak Reverse Voltage V_{RWM} (V)	Maximum Reverse Surge Current I_{PP} (A)	Maximum Clamping Voltage V_C @ I_{PP} (V)
	Bi	Min (V)	Max (V)	I_T (mA)				
SMAJ40CA	YR	44.40	49.10	1	1	40.0	6.20	64.5
SMAJ43CA	YT	47.80	52.80	1	1	43.0	5.76	69.4
SMAJ45CA	YV	50.00	55.30	1	1	45.0	5.50	72.7
SMAJ48CA	YX	53.30	58.90	1	1	48.0	5.17	77.4
SMAJ51CA	YZ	56.70	62.70	1	1	51.0	4.85	82.4
SMAJ54CA	ZE	60.00	66.30	1	1	54.0	4.59	87.1
SMAJ58CA	ZG	64.40	71.20	1	1	58.0	4.27	93.6
SMAJ60CA	ZK	66.70	73.70	1	1	60.0	4.13	96.8
SMAJ64CA	ZM	71.10	78.60	1	1	64.0	3.88	103.0
SMAJ70CA	ZP	77.80	86.00	1	1	70.0	3.54	113.0
SMAJ75CA	ZR	83.30	92.10	1	1	75.0	3.31	121.0
SMAJ78CA	ZT	86.70	95.80	1	1	78.0	3.17	126.0
SMAJ80CA	ZB	88.80	97.60	1	1	80.0	3.09	129.6
SMAJ85CA	ZV	94.40	104.00	1	1	85.0	2.92	137.0
SMAJ90CA	ZX	100.00	111.00	1	1	90.0	2.74	146.0
SMAJ100CA	ZZ	111.00	123.00	1	1	100.0	2.47	162.0
SMAJ110CA	VE	122.00	135.00	1	1	110.0	2.26	177.0
SMAJ120CA	VG	133.00	147.00	1	1	120.0	2.07	193.0
SMAJ130CA	VK	144.00	159.00	1	1	130.0	1.91	209.0
SMAJ140CA	VB	155.00	171.00	1	1	140.0	1.76	226.8
SMAJ150CA	VM	167.00	185.00	1	1	150.0	1.65	243.0
SMAJ160CA	VP	178.00	197.00	1	1	160.0	1.54	259.0
SMAJ170CA	VR	189.00	209.00	1	1	170.0	1.45	275.0
SMAJ180CA	VT	200.00	220.00	1	1	180.0	1.37	291.6
SMAJ190CA	VV	211.00	232.00	1	1	190.0	1.30	307.8
SMAJ200CA	VW	224.00	247.00	1	1	200.0	1.23	324.0
SMAJ220CA	VX	246.00	272.00	1	1	220.0	1.12	356.0
SMAJ250CA	VZ	279.00	309.00	1	1	250.0	0.99	405.0
SMAJ300CA	HE	335.00	371.00	1	1	300.0	0.82	486.0
SMAJ350CA	HG	391.00	432.00	1	1	350.0	0.71	567.0
SMAJ400CA	HK	447.00	494.00	1	1	400.0	0.62	648.0
SMAJ440CA	HM	492.00	543.00	1	1	440.0	0.56	713.0

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善，ChipNobo 有权调整产品指标和部分技术参数的升级，所出现信息披露过程存在延后或者不能送达的情形，ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用，不支持确有制裁地区的敏感项目和特殊设备，ChipNobo 有限公司或其代表，对因不当使用而造成的任何损害不承担任何责任。

For additional information, please visit our website <http://www.chipnobo.com>, or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息，请访问我们的网站 <http://www.chipnobo.com>，或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。