




佳恩半导体  
JIAENSEMI

JNG50T120QMU2

## IGBT

### Features

- 1200V,50A
- $V_{CE(sat)(typ.)}=1.55V$  @  $V_{GE}=15V$ ,  $I_c=50A$
- Positive temperature coefficient
- Fast Switching
- Reliable and Rugged
- Halogen Free and Green Devices Available



TO-247-3L Plus

### General Description

JIAEN Trench IGBTs offer lower losses and higher energy efficiency for application such as UPS, Motor drives, PFC, Portable power station and other soft switching applications.

### Absolute Maximum Ratings

Symbol	Parameter	Value	Units
$V_{CES}$	Collector-Emitter Voltage	1200	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 30$	V
$I_c$	Continuous Collector Current ( $T_c=25\text{ }^\circ\text{C}$ )	100	A
	Continuous Collector Current ( $T_c=100\text{ }^\circ\text{C}$ )	50	A
$I_{CM}$	Pulsed Collector Current (Note 1)	200	A
$I_F$	Diode Continuous Forward Current ( $T_c=100\text{ }^\circ\text{C}$ )	50	A
$I_{FM}$	Diode Maximum Forward Current (Note 1)	100	A
$t_{sc}$	Short Circuit Withstand Time	8	us
$P_D$	Maximum Power Dissipation ( $T_c=25\text{ }^\circ\text{C}$ )	833	W
$T_J$	Operating Junction Temperature Range	-55 to +175	$^\circ\text{C}$

### Thermal Characteristics

Symbol	Parameter	Max.	Units
$R_{th\ j-c}$	Thermal Resistance, Junction to case for IGBT	0.18	$^\circ\text{C}/\text{W}$
$R_{th\ j-c}$	Thermal Resistance, Junction to case for Diode	0.37	$^\circ\text{C}/\text{W}$
$R_{th\ j-a}$	Thermal Resistance, Junction to Ambient	40	$^\circ\text{C}/\text{W}$



佳恩半导体  
JIAENSEMI

JNG50T120QMU2

## Electrical Characteristics ( $T_c=25^\circ C$ unless otherwise noted )

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$BV_{CES}$	Collector-Emitter Breakdown Voltage	$V_{GE}=0V, I_C=1mA$	1200	-	-	V
$I_{CES}$	Collector-Emitter Leakage Current	$V_{CE}=1200V, V_{GE}=0V$	-	-	10	uA
$I_{GES}$	Gate Leakage Current, Forward	$V_{GE}=\pm 20V, V_{CE}=0V$	-	-	$\pm 200$	nA
$V_{GE(th)}$	Gate Threshold Voltage	$V_{GE}=V_{CE}, I_C=250\mu A$	4.93	-	6.93	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$V_{GE}=15V, I_C=50A$	-	1.55	-	V
$Q_g$	Total Gate Charge	$V_{CC}=960V$ $V_{GE}=15V$ $I_C=50A$	-	291	-	nC
$Q_{ge}$	Gate-Emitter Charge		-	81	-	nC
$Q_{gc}$	Gate-Collector Charge		-	110	-	nC
$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=600V$ $V_{GE}=15V$ $I_C=50A$ $R_G=5\Omega$ Inductive Load $T_c=25^\circ C$	-	44	-	ns
$t_r$	Turn-on Rise Time		-	95	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	190	-	ns
$t_f$	Turn-off Fall Time		-	264	-	ns
$E_{on}$	Turn-on Switching Loss		-	2.57	-	mJ
$E_{off}$	Turn-off Switching Loss		-	3.73	-	mJ
$E_{ts}$	Total Switching Loss		-	6.31	-	mJ
$C_{ies}$	Input Capacitance	$V_{CE}=25V$ $V_{GE}=0V$ $f = 1MHz$	-	8408	-	pF
$C_{oes}$	Output Capacitance		-	197	-	pF
$C_{res}$	Reverse Transfer Capacitance		-	55	-	pF

## Electrical Characteristics of Diode ( $T_c=25^\circ C$ unless otherwise noted )

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_F$	Diode Forward Voltage	$I_F=50A$	-	2.0	3.5	V
$t_{rr}$	Diode Reverse Recovery Time	$V_{CE} = 600V$ $I_F= 50A$	-	94	-	ns
$I_{rr}$	Diode peak Reverse Recovery Current		-	9.7	-	A
$Q_{rr}$	Diode Reverse Recovery Charge		-	225	-	nC

### Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature



## Typical Performance Characteristics

Figure 1: Power Dissipation




Figure 2: Collector Current vs. Case Temperature




Figure 3: Safe Operation Area




Figure 4: Typical Transfer Characteristics






Figure 5: Typical Output Characteristics




Figure 6: Typical Output Characteristics




Figure 7: Typical Collector-Emitter Saturation Voltage vs. Junction Temperature






Figure 8: Typical Gate-Emitter Threshold Voltage vs. Junction Temperature







**Figure 9: Typical Switching Times vs. Gate Resistor ( $T_J=25^\circ\text{C}$ ,  $V_{CE}=600\text{V}$ ,  $V_{GE}=15\text{V}$ ,  $I_c=50\text{A}$ )**




**Figure 10: Typical Switching Energy vs. Gate Resistor ( $T_J=25^\circ\text{C}$ ,  $V_{CE}=600\text{V}$ ,  $V_{GE}=15\text{V}$ ,  $I_c=50\text{A}$ )**



**Figure 11: Typical Switching Times vs. Junction Temperature ( $V_{CE}=600\text{V}$ ,  $V_{GE}=15\text{V}$ ,  $I_c=50\text{A}$ ,  $Rg=5\Omega$ )**




**Figure 12: Typical Switching Energy vs. Junction Temperature ( $V_{CE}=600\text{V}$ ,  $V_{GE}=15\text{V}$ ,  $I_c=50\text{A}$ ,  $Rg=5\Omega$ )**







**Figure 13: Typical Switching Times vs. Collector Current ( $T_J=25^\circ\text{C}$ ,  $V_{CE}=600\text{V}$ ,  $V_{GE}=15\text{V}$ ,  $R_g=5\Omega$ )**



**Figure 14: Typical Switching Energy vs. Collector Current ( $T_J=25^\circ\text{C}$ ,  $V_{CE}=600\text{V}$ ,  $V_{GE}=15\text{V}$ ,  $R_g=5\Omega$ )**



**Figure 15: Typical Switching Energy vs.  $V_{CE}$  ( $T_J=25^\circ\text{C}$ ,  $V_{GE}=15\text{V}$ ,  $I_c=50\text{A}$ ,  $R_g=5\Omega$ )**



**Figure 16: Typical Switching Energy vs.  $V_{CE}$  ( $T_J=25^\circ\text{C}$ ,  $V_{GE}=15\text{V}$ ,  $I_c=50\text{A}$ ,  $R_g=5\Omega$ )**






Figure 17: Typical Capacitance vs. Collector- Emitter Voltage




Figure 18: Typical Gate Charge




Figure 19: IGBT Transient Thermal Impedance vs. Pulse Width






Figure 20: Diode Transient Thermal Impedance vs. Pulse Width





**Figure 21: Typical Diode Forward Current vs. Forward Voltage**






佳恩半导体  
JIAENSEMI

**JNG50T120QMU2**

## TO-247Plus PACKAGE OUTLINE



Symbol	单位 mm		
	Min	Nom	Max
A	4.80	5.00	5.20
A1	2.80	3.0	3.20
A2	1.80	2.0	2.20
b	1.00	1.20	1.40
b1	2.90	3.10	3.30
b2	1.90	2.10	2.30
b3	3.90	4.10	4.30
c	0.45	0.60	0.75
e	5.25	5.45	5.65
E	15.6	15.8	16.0
E1	10.2	10.6	11.0
E2	6.30	6.06	6.90
E3	1.60	1.80	2.00
L1	0.35	0.50	0.65
L2	1.80	2.00	2.20
L3	9.50	10.0	10.5
H	20.5	21.0	21.5
H1	19.5	20.0	20.5
H2	3.50	4.00	4.50



佳恩半导体  
JIAENSEMI

**JNG50T120QMU2**

## **Disclaimers**

JIAEN Semiconductor Co., Ltd reserves the right to make changes without notice in order to improve reliability, function or design and to discontinue any product or service without notice. Customers should obtain the latest relevant information before orders and should verify that such information is current and complete. All products are sold subject to JIAEN's terms and conditions supplied at the time of order acknowledgement.

JIAEN Semiconductor Co., Ltd warrants performance of its hardware products to the specifications at the time of sale. Testing, reliability and quality control are used to the extent JIAEN deems necessary to support this warranty. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

JIAEN Semiconductor Co., Ltd does not assume any liability arising from the use of any product or circuit designs described herein. Customers are responsible for their products and applications using JIAEN's components. To minimize risk, customers must provide adequate design and operating safeguards.

JIAEN Semiconductor Co., Ltd does not warrant or convey any license either expressed or implied under its parent rights, nor the rights of others. Reproduction of information in JIAEN's datasheets or data books is permissible only if reproduction is without modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice. JIAEN Semiconductor Co., Ltd is not responsible or liable for such altered documentation.

Resale of JIAEN's products with statements different from or beyond the parameters stated by JIAEN Semiconductor Co., Ltd for that product or service voids all express or implied warranties for the associated JIAEN's product or service and is unfair and deceptive business practice. JIAEN Semiconductor Co., Ltd is not responsible or liable for any such statements.